




PS MANUAL

BCD WORKSHOP BATTERY CHARGERS

1.0 Model **BCD-A1225**

2.0 Description

12 Volt 25Amp Fully Automatic SmartCharger Workshop Battery Charger



Durst Industries Australia Pty. Ltd.

durst.com.au

Phone: +61 2 9660 1755

Unit 1, 11 Packard Avenue
Castle Hill NSW 2154 Australia





3.0 Features

- Fully Automatic, Fast and Safe.
- Overcharging Protection: Yes
- Short Circuit, Spike and Surge Suppression
- Three stage Charging indicator LED's
- Eliminates Sulphation
- Compact and Lightweight
- Heavy Duty Leads and Battery Clamps
- Comfortable Lifting Handle, Rubber Buffers and Cable Winders
- Powder Coated Steel Casing
- Australian Electrical Standard & EMC Compliant

4.0 Physical and Dimensional Properties

- Each unit weighs approximately 4.75 Kg
- Width 180 mm
- Length 265 mm
- Height 100 mm
- Carton Dimensions: 300mm x 210mm x 215mm

5.0 Performance

- Input Voltage 200 - 240 Volt
- Frequency 47 Hz – 63 Hz
- Battery Size Ahr: 60Ah - 300Ah
- Current @ 12 Volts: 25 Amps Dual
- Number of Channels 2
- Charging Voltage 14.4 VDC to suit GEL AGM Flooded Calcium
- Float Charge 13.7 VDC to suit GEL AGM Flooded Calcium
- Wattage Output 367W

6.0 Uses

- Premium SmartCharger Battery Charger.
- Suitable for Automotive, Marine, Mobile Home or Caravan, Mobility Appliances, Solar, Deep Cycle Batteries, 4X 4 Vehicles.

7.0 Documentation

- Bar Code No: **9346080001195**
- Product Specification Manual - PS 118
- Work Instruction Manual - WI 118
- Product Costing Manual - PC 118

