



PS MANUAL

SMARTWASHER®

1.0 Model

DSW-123MSK

2.0 Description

1 x Mobile SmartWasher® 123M + 3 x Tubs of OzzyJuice® + 1 x FL4 OzzyMat™ Filter



Durst Industries Australia Pty. Ltd.

durst.com.au

Phone: +61 2 9660 1755

Unit 1, 11 Packard Avenue
Castle Hill NSW 2154 Australia





3.0 Features

- ON/OFF control, side mounted
- Flow timer with 10 and 30 minute increments
- Flow through parts brush
- User regulated independent flow control from brush or nozzle
- Thermostat maintains fluid at 42° C (adjustable to 46° C)
- Does not damage Neoprene or Rubber gaskets and seals
- Indicators: Low Fluid level indicator (**Red**)
Standby/ ready indicator (**Green**)
Power Indicator (**Green**)
- Complies with Australian WHS Regulations
- Patented as a non-hazardous bio remediating parts cleaning system
- Uses warm aqueous degreasing solution called " Ozzy Juice®"
- Reduces the release of VOC's and eliminates hazardous waste.
- Helps save our environment whilst protecting the health and wellbeing of your employees.

SmartWasher® Certificates and Approvals



AQMD Certified
DSW-SW3 Truck Grade OzzyJuice®.
DSW-SW6-8 Weapons Aviation Grade OzzyJuice®.



Authorization to Mark



Declaration of Conformity



Test Certificate in Compliance with the Device Safety Act



Test Certificate in Compliance with the Device Safety Act
National Sanitation Foundation. DSW-SW3, DSW-SW6-8 OzzyJuice®



Product Safety Certificate

4.0 Physical and Dimensional Properties

- Each unit weighs approximately 33.0Kg Empty
- Approximate Shipping Weight: 113.0Kg
- Material: Blow moulded High Density polyethylene



PS MANUAL

Overall Dimensions

- Width 685 mm
- Length 1090 mm
- Height 1050 mm

Inside Sink Dimensions

- Width 590 mm
- Length 650 mm
- Height 204 mm

Shipping Dimensions

- Width 712 mm
- Length 1230 mm
- Height 1130 mm

5.0 Performance

- Pump Capacity: 93.75 Kw; 170 GPH at 1 foot; sump intake – see **DSW-PU20**
- Electrical: 240 Volt, 50 Hz
- Heater: 1000 Watt industrial Heater –see **DSW-1285**
- Capacity: Holds 250Kg Load
- Filtration: Microbe impregnated 50 micron filters changeable and disposable without special tools or equipment. – see **DSW-FL4-3PK**
- Cleaning Solution: OzzyJuice® – see **DSW-SW3** and **MSDS SW3**
Aqueous based surfactant cleaner.
NO Flashpoint
PH Neutral biodegradable
Non-Toxic, no caustic, non flammable, non hazardous
NO VOC's, Phosphates, formaldehyde, bio solvents or solvents.
- Microbe Treatment: Ozzy Booster™ - see **DSW-1070**
Environmental- shock resistant;
Preserved for minimum 18 months shelf life.
Natural occurring, non- pathogenic microbes

6.0 Uses

- Suitable for Car/Truck dealer workshops, Panel Beaters, Bus repairers, Mining Companies, Aviation, Defence, Councils, TAFE,

7.0 Documentation

- Bar Code Number: **9346080000211**
- Product Specification Manual - PS 95
- Work Instruction Manual - WI 95
- Product Costing Manual - PC 95

